

PUNCHING DEVICE, SHEET PROCESSOR HAVING THE PUNCHING  
DEVICE, AND IMAGE FORMING APPARATUS HAVING THE  
PUNCHING DEVICE

5 BACKGROUND OF THE INVENTION

Field of the Invention

20,400,000-434,600  
The present invention relates to a punching  
device for punching holes in a thin member, e.g., a  
board or a plate such as a wooden board or an iron  
10 plate, or a sheet of some material, a sheet processor  
having the punching device provided in its main body,  
and an image forming apparatus also having the  
punching device provided in its main body.

Related Background Art

15 Conventionally, punching devices have been used  
singly or as a component in a state of being  
incorporated in an apparatus with which a thin member  
to be punched is handled.

For example, an application of a punching device  
20 in a sheet processor for binding or folding punched  
sheets is known. The punching device is used in a  
state of being incorporated in the main body of the  
sheet processor. An application of a punching device  
in an image forming apparatus such as a copying  
25 machine, a laser beam printer, a facsimile machine,  
or a combination of some of these apparatuses is  
known. The punching device is used as a component in

a state of being incorporated in a main body of the image forming apparatus. Further, in some cases, a punching device is used in a state of being incorporated in a sheet processor and incorporated in  
5 a main body of an image forming apparatus together with the sheet processor.

A punching device used to make holes in a member has the number of punches and the same number of dies corresponding to a certain number of holes which  
10 should be made in the member by punching. The punching device punches holes in the member by causing each punch to advance into the hole in the corresponding die.

Conventional punching devices, however, have a  
15 complicated mechanism for operating each punch and are therefore incapable of punching holes in a member smoothly and quickly.

In recent years, there has been an increasing demand for changing the number of holes to be punched  
20 in a member in accordance with the size thereof. It is not possible to satisfy the demand by using any of the conventional punching devices since each conventional punching device has only punches and dies corresponding to the number of holes to be  
25 punched in a member.

# SUMMARY OF THE INVENTION

The present invention has been made in view of the above, and an object of the present invention is to provide a punching device capable of smoothly  
5 punching holes and changing the number of holes to be punched and, in particular, capable of quickly changing the number of holes to be punched, a sheet processor having the punching device, and an image forming apparatus having the punching device.

10 In order to achieve the above-mentioned object, one aspect of the present invention relates to a punching device, comprising:

- a die member having a plurality of die holes formed therein;
- 15 a plurality of punch members which are caused to advance into the die holes to punch holes in a member to be punched;
- an operating member having cam portions formed along a direction intersecting the direction of  
20 advancement of the punch members, the operating member being moved along the direction intersecting the direction of advancement of the punch members to cause by a conversion function of the cam portions the punch members to advance into the die holes; and
- 25 drive means for selectively causing advancement of the plurality of punch members by changing the direction of movement of the operating member.

10091454-030702

204050-4945001

In a punching device according to another aspect of the invention, each of the cam portions has a straight groove and a cam groove for performing the conversion function, and when the operating member is moved in one of opposite directions, at least one of the cam grooves of the cam portions acts on one of the punch members selectively to cause the same to advance.

In a punching device according to another aspect of the invention, one of the cam portions has two cam grooves at its center, and straight grooves formed at opposite ends of each cam groove, and is used to control two of the punch members.

In a punching device according to another aspect of the invention, one of the cam portions has one cam groove at its center, and straight grooves formed at opposite ends of the cam groove, and is used to control two of the punch members.

In a punching device according to another aspect of the invention, one of the cam portions has one cam groove at its end, and a straight groove formed at an end of the cam groove, and is used to control one of the punch members.

In a punching device according to another aspect of the invention, one of the cam portions has two cam grooves at its center, and straight grooves formed at opposite ends of each cam groove, and is used to

control two of the punch members; another of the cam  
portions has one cam groove at its center, and  
straight grooves formed at opposite ends of the cam  
groove, and is used to control two of the punch  
5 members; and a remaining one of the cam portions has  
one cam groove at its end, and a straight groove  
formed at an end of the cam groove, and is used to  
control one of the punch members, two of the punch  
members and three of the punch members being  
10 selectively caused to advance.

Another aspect of the present invention relates  
to a punching device, comprising position detection  
means for detecting the position of the operating  
member while sectioning the area for movement of the  
15 operating member into a first rest area, a first  
punching area, a second punching area, and a second  
rest area in the stated order, drive means for moving  
the operating member, and operation control means for  
controlling the drive means on the basis of the  
20 detection operation of the position detection means,  
wherein the operating member can be moved between the  
first rest area and the second rest area, which  
performs in the first punching area a punching  
operation for causing the punch member to advance  
25 into the corresponding die hole when moved from the  
first rest area to the second rest area, and performs  
in the second punching area a punching operation for

20250714-03070

causing the punch member to advance into the corresponding die hole when moved from the second rest area to the first rest area.

In a punching device according to another aspect  
5 of the invention, the operation control means performs an initializing operation for moving the operating member to the second rest area when the operating member is located in the first rest area or in the first punching area, and that for moving the  
10 operating member to the first rest area when the operating member is located in the second rest area or in the second punching area.

Another aspect of the present invention relates to a punching device, comprising position detection  
15 means for detecting the position of the operating member while sectioning the area for movement of the operating member into a first rest area, a first punching area, a second punching area, a second rest area, a third punching area, a fourth punching area,  
20 and a third rest area in the stated order, and operation control means for moving the operating member through a movement area selected from a first movement area formed of the first rest area, the first punching area, the second punching area, and  
25 the second rest area, and a second movement area formed of the second rest area, the third punching area, the fourth punching area, and the third rest

20250715-0001

area by controlling the drive means on the basis of the detection operation of the position detection means, wherein the operating member punches a first number of holes in the member to be punched with the corresponding number of the punches when the operating member performs in the first punching area a punching operation for causing the corresponding number of the punch members to advance into the corresponding die holes during its movement from the first rest area to the second rest area, and when the operating member performs in the second punching area a punching operation for causing the corresponding number of the punch members to advance into the corresponding die holes during its movement from the second rest area to the first rest area, and wherein the operating member punches a second number of holes in the member to be punched with the corresponding number of the punches when the operating member performs in the third punching area a punching operation for causing the corresponding number of the punch members to advance into the corresponding die holes during its movement from the second rest area to the third rest area, and when the operating member performs in the fourth punching area a punching operation for causing the corresponding number of the punch members to advance into the corresponding die holes during its movement from the third rest area to

20240504-0300

In a punching device according to another aspect of the invention, the operation control means performs, on the basis of the detection operation of the position detection means, an initializing operation for moving the operating member to the second rest area when the operating member is located in the first rest area or in the first punching area, that for moving the operating member to the first rest area when the operating member is located in the second rest area or in the second punching area, that for moving the operating member to the third rest area when the operating member is located in the second rest area or in the third punching area, and that for moving the operating member to the second rest area when the operating member is located in the third rest area or in the fourth punching area.

In a punching device according to another aspect of the invention, a speed of the movement of the operating member in the initializing operation is  
20 lower than that in the punching operation.

In a punching device according to another aspect of the invention, the operation control means stops the operation of the drive means if the position detection means does not detect the movement of the operating member after a lapse of a predetermined period of time from the time at which the operation



control means starts the operation of the operating member.

In a punching device according to another aspect of the invention, the predetermined period of time in  
5 the case of the initializing operation is longer than that in the case of the punching operation.

In order to achieve the above-mentioned object, the present invention relates to a sheet processor, comprising the punching device for punching holes in  
10 the sheet according to any one of the above aspects and binding means for binding the sheets.

In order to achieve the above-mentioned object, the present invention relates to an image forming apparatus, comprising: image forming means for  
15 forming an image on a sheet; and the punching device for punching holes in the sheet according to any one of the above aspects.

In order to achieve the above-mentioned object, the present invention relates to an image forming  
20 apparatus, comprising: image forming means for forming an image on a sheet; the punching device for punching holes in the sheet according to any one of the above aspects; and binding means for binding the sheets.

25 The punching device of the present invention is arranged to punch holes in a member to be punched by using the movement of the operating member moved in a

2020091454-030702

5 punched.

10 member to be punched with only one punching device of  
the present invention.

15 After initialization, therefore, the operating member  
can be quickly moved to one of the punching areas  
with reliability to quickly perform the punching  
operation with reliability.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic sectional front view of a copying machine which is an image forming apparatus having a sheet processor, and which represents an embodiment of the present invention;

25            Fig. 2A is a top view of the punching device in  
the embodiment shown in Fig. 1;

Fig. 2B is a diagram showing a view of the

punching device as seen from the sheet conveyance direction upstream side in the embodiment shown in Fig. 1;

Fig. 2C is a cross-sectional view of the punching device taken along a cam member in the embodiment shown in Fig. 1;

Fig. 3 is a side view as seen from the right-hand side of the punching device shown in Fig. 2B, with some portion removed;

Fig. 4 is a side view as seen from the right-hand side of the punching device shown in Fig. 2B;

Fig. 5 is a diagram showing the configuration of a controller for controlling the punching device;

Figs. 6A, 6B, 6C and 6D are diagrams for explaining two holes punching operation;

Figs. 6D, 6E, 6F and 6G are diagrams for explaining three holes punching operation;

Fig. 7 is a diagram showing an ON/OFF logic of each cam member detection sensor;

Fig. 8 is a flowchart of the operation of the punching device in the embodiment of the present invention;

Fig. 9 is a flowchart of an initializing operation of the punching device in the embodiment of the present invention;

Fig. 10 is a diagram in matrix form showing destinations for the cam member in the initializing

20250414 1600

operation of the punching device in the embodiment of the present invention;

Fig. 11 is a flowchart of a three holes punching operation of the punching device in the embodiment of  
5 the present invention;

Fig. 12 is a flowchart of a two holes punching operation of the punching device in the embodiment of the present invention; and

Fig. 13 is a flowchart of a two holes/three  
10 holes switching operation of the punching device in the embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

An image forming apparatus which represents an  
15 embodiment of the present invention, which is, typically, a printer, and which includes a punching device and a sheet processor will be described with reference to the accompanying drawings.

The present invention will be described below  
20 with respect to a case of punching holes in a sheet. However, the punching device of this embodiment is capable of punching holes a thin member (member which should be punched), e.g., a board or a plate such as a wooden board or an iron plate, or a sheet of some  
25 material. Therefore punching with the punching device of the present invention is not limited to punching on a sheet only.

20240304-030702

The punching device is used singly or as a portion of an apparatus with which a sheet is handled, i.e., in a state of being incorporated in the apparatus. The apparatus with which a sheet is  
5 handled is, for example, a sheet processor for binding or folding punched sheets or an image forming apparatus for forming an image on a sheet. Examples of the image forming apparatus are a copying machine, a laser beam printer, a facsimile machine, and a  
10 combination of some of these apparatuses. Examples of sheets punched by the punching device are ordinary paper, an overhead projector sheet, a thin resin sheet used as a substitute for ordinary paper, and a cardboard.

15 (Copying machine)

A copying machine which is an example of the image forming apparatus incorporating the punching device will be described with reference to Fig. 1.

Referring to Fig. 1, a copying machine 3 has a  
20 sheet processor 1 connected to a copying machine main unit 2. The sheet processor 1 has a punching device 50 capable of punching holes in a sheet on which an image is formed in the copying machine main unit 2, and a finisher 4 capable of sheet post-processing for  
25 binding each of certain numbers of copies.

The copying machine 3 optically reads through an optical portion 6 an original which is automatically

20240507-154400

fed from an original feeder 5 provided at the top. A digital signal thereby obtained as information on the original is transmitted to an image forming portion (image forming means) 7. An irradiating portion 7a  
5 irradiates a photosensitive drum 7b with laser light to form a latent image on the same. This latent image is developed by a developing device 7c to form a toner image.

A plurality of sheet cassettes 8 in which sheets  
10 P of various sizes are accommodated are provided in a lower section of the copying machine main unit 2. The toner image is transferred by an electrophotographic process onto a sheet conveyed from one of the sheet cassettes 8 by a pair of conveying rollers 9. The  
15 sheet is conveyed to a fixing device 10. The toner image is fixed on the sheet by heat and pressure in the fixing device 10.

If a mode of forming an image on one sheet surface has been selected, the sheet is conveyed to  
20 the sheet processor 1. If two images are to be formed on the two surfaces of the sheet, the sheet is conveyed into a reconveying path 11 by a switchback mechanism to be again conveyed to the image forming portion 7, and an image is formed on the other  
25 surface of the sheet. Thereafter the sheet is conveyed to the sheet processor 1. A sheet may also be supplied through a manual insertion tray 12. The

2025 RELEASE UNDER E.O. 14176

components of the copying machine main unit 2 are controlled by a control device 14.

(Sheet processor)

Referring to Fig. 1, a pair of rollers 20 at an entrance of the sheet processor 1 receive sheet P discharged from a pair of discharging rollers 13. The received sheet P is conveyed by a pair of first conveying rollers 21. Passage of sheet P is detected by a sheet detection sensor 22.

Thereafter, a rear end portion of the sheet is punched by the punching device 50, and the sheet is temporarily retained on a roll surface of a buffer roller 23 having a comparatively large diameter by pressing rollers 24, 25, and 26 provided on the periphery of the roller 23, the sheet being pressed against the roller surface by the pressing rollers 24, 25, and 26.

A first switching flapper 27 operates for selection between a non-sort path 28 and a sort path 29. A second switching flapper 30 operates for selection between the sort path 29 and a buffer path 31 for temporarily retaining sheet P.

Sheet P in the non-sort path 28 is detected by a sensor 32. Sheet P in the buffer path 31 is detected by a sensor 33. Sheet P in the sort path 29 is conveyed by a pair of second conveying rollers 34.

A processing tray unit 35 temporarily stacks and

10091464-030702

jogs sheets P. The processing tray unit 35 has an intermediate tray 38 provided for the purpose of performing stapling processing with stapler 37 in a staple unit (binding means) 36. One of a pair of  
5 batch discharging rollers 39, i.e., a lower discharging roller 39a on a fixed side in this arrangement, is placed at a discharge end of the intermediate tray 38.

Sheet P is discharged onto the intermediate tray  
10 38 by a pair of first discharging rollers 40 placed at an outlet of the sort path 29. Also, sheet P is discharged onto a sample tray 42 by a pair of second discharging rollers 41 placed at an outlet of the non-sort path 28.

15 The upper discharging roller 39b in the pair of batch discharging rollers 39 is supported on a swingable guide 43. When the swingable guide 43 is swung to a closing position, it is brought into pressure contact with the discharging roller 39a to  
20 discharge sheet P from the intermediate tray 38 onto a stack tray 44.

A batch stack guide 45 receives trailing-end edges (rear ends as viewed along the batch discharge direction) of a batch of sheets stacked on the stack  
25 tray 44 and the sample tray 42. In this embodiment, the batch stack guide 45 also forms part of the casing of the sheet processor 1. The operations of

202002-4346007



The spacers 61 are provided between the lower frame 60 and the upper frame 62 to form a gap S between a top plate 63 of the lower frame 60 and a bottom plate 64 of the upper frame 62 through which a sheet is allowed to pass. The upstream ends of the

top plate 63 of the lower frame 60 and the bottom plate 64 of the upper frame 62 are formed so as to be gradually distanced apart from each other, as shown in Fig. 3. The upstream ends of the top plate 63 and  
5 the bottom plate 64 thus formed have the function of guiding a sheet into the gap S.

The upper frame 62 has the bottom plate 64, a top plate 66 opposed to the bottom plate 64, and a back plate 67 which connects the bottom plate 64 and  
10 the top plate 66. These plates form the shape of a box opened at one side as viewed in cross section. Five punches 68A, 68B, 68C, 68D, and 68E are mounted in the bottom and top plates 64 and 66 so as to be able to move along a vertical direction through the  
15 bottom and top plates 64 and 66. Die holes 70A, 70B, 70C, 70D, and 70E for punching holes in a sheet in cooperation with the punches 68A, 68B, 68C, 68D, and 68E are formed in the top plate 63 of the lower frame 60 facing the lower ends of the punches 68A, 68B, 68C,  
20 68D, and 68E. Thus the top plate 63 of the lower frame 60 functions both as a die and as a sheet guide plate.

The punches 68A, 68B, 68C, 68D, and 68E are separated into a group consisting of the punches 68A,  
25 68B, and 68C for punching three holes, arranged at equal intervals in the upper frame 62, and another group consisting of the punches 68D and 68E for

punching two holes, disposed between the punches 68A, 68B, and 68C for punching three holes. The punches 68A, 68B, 68C, 68D, and 68E respectively have engaging pins 75 which engage cams 73A, 73B, 73C, 73D, 5 and 73E in a cam member 72, the engaging pins 75 extending perpendicularly from the punches 68A, 68B, 68C, 68D, and 68E.

20,000-1544600F

The cams 73A, 73B, 73C, 73D, and 73E formed in the cam member 72 are separated into a group 10 consisting of the cams 73A, 73B, and 73C for punching three holes, and another group consisting of the cams 73D and 73E for punching two holes. Each of the cams 73A, 73B, 73C, 73D, and 73E is a groove formed of slanted portions slanted in different directions and 15 straight portions extending along the direction of movement of the cam member 72, the slanted portions having their adjacent ends connected smoothly, each slanted portion and one of the straight portions also having their adjacent ends connected smoothly. Since 20 the engaging pins 75 of the punches 68A, 68B, 68C, 68D, and 68E engage the cams 73A, 73B, 73C, 73D, and 73E, the position of each of the punches 68A, 68B, 68C, 68D, and 68E in the axial direction is determined by the position of its pin in one of the 25 cams.

Referring to Figs. 2A to 2C, the punch 68A in the three-holes-punching punch group engages the cam

73A at the left end in the three-holes-punching cam group. The right straight portion of the cam 73A is formed so as to be longer than the left straight portion. The second cam 73B (73D) from the left is  
5 used in three holes punching and also used in two holes punching, and the central punch 68B in the three-holes-punching punch group and the left punch 68D in the two-holes-punching punch group engage the cam 73B (73D). The arrangement in which the cam 73B  
10 (73D) is used in common with the two punches 68B and 68D has the effects of reducing the number of cams and reducing the distance between the punches 68B and 68D. The third cam 73E from the left used in two holes punching and the fourth cam 73C from the left  
15 used in three holes punching have their straight portions formed continuously with each other. The right punch 68E used in two holes punching engages the third cam 73E from the left used in two holes punching. The right punch 68C used in three holes  
20 punching engages the fourth cam 73C from the left used in three holes punching. The outer straight portions of these two cams 73E and 73C extend away from each other.

In the above-described cams, the length of the  
25 right straight portion of the left-end cam 73A used in three holes punching, the length of the right and left straight portions of the second cam 73B (73D)

2020ED-434600F

from the left used in three holes punching and in two  
holes punching, the length of the left straight  
portion 79E of the third cam 73E from the left used  
in two holes punching, and the length of the right  
5 straight portion of the fourth cam 73C from the left  
used in three holes punching are set to values  
substantially equal to each other. The left cam 73A  
used in three holes punching, the third cam 73E from  
the left used in two holes punching, and the fourth  
10 cam 73C from the left used in thee hole punching are  
formed at the same height. The second cam 73B (73D)  
from the left used in three holes punching and in two  
holes punching is formed at a height higher than that  
of the other three cams, as viewed in Fig. 2B or 2C.

15 Therefore, the end of the right straight portion  
of the left cam 73A used in three holes punching and  
the end of the left straight portion of the second  
cam 73B (73D) from the left used in three holes  
punching and in two holes punching can be formed in  
20 such positions as to face each other in the vertical  
direction as viewed in Fig. 2B or 2C. Also, the  
entire right straight portion 78E of the second cam  
73B (73D) from the left used in three holes punching  
and in two holes punching and the entire left  
25 straight portion of the third cam 73E from the left  
used in two holes punching can be formed generally in  
such positions as to face each other. Thus, the

20250404 14:03:02

punches 68A, 68B, 68C, 68D, and 68E can be disposed by setting standard distances therebetween.

Since the positions of the cams 73A, 73B, 73C, 73D, and 73E are shifted along the direction of movement of the punches 68A, 68B, 68C, 68D, and 68E to separately form the cams, it can be avoided that the unnecessary punches are operated.

Further, while the punches 68A, 68B, and 68C are disposed at equal intervals, the distance between the left cam 73A used in three holes punching and the second cam 73B (73D) from the left used in three holes punching and in two holes punching and the distance between the cam 73B (73D) and the fourth cam 73C from the left used in three holes punching are different from each other. Also, the distance between the punches for three holes punching and the corresponding distance between the cams for three holes punching are different from each other.

Similarly, the distance between the punches 68D and 68E for two holes punching and the distance between the cams 73D and 73E for two holes punching are different from each other. The distances between the cams and the distances between the punches are varied as described above in order that the three punches for three holes punching or the two punches for two holes punching operate successively with a time lag to punch holes in a sheet as the cam member 72 is

moved to perform three holes punching or two holes punching with the punches. As a result, a cam member drive motor 92 described below can smoothly operate for punching without any excessive load imposed thereon.

A rack 91 is formed in a right end portion of the cam member 72. A pinion 94, which is rotated by the cam member drive motor 92 provided on the movable frame 52, meshes with the rack 91.

Three punching state detection flags (position detection means) 101, 102, and 103 are formed on the right end portion of the cam member 72 so as to project upward. A cam member home position detection sensor (position detection means) 56 for detecting each of the three punching state detection flags 101, 102, and 103 is provided on the top plate 66 of the upper frame 62. The three punching state detection flags 101, 102, and 103 and the cam member home position detection sensor 56 are arranged to detect whether two or three of the punches 68A, 68B, 68C, 68D, and 68E are punching holes in a sheet. Hereinafter, a home position will be referred to as "HP".

A cam member state detection flag (position detection means) 105 is formed on the right end portion of the cam member 72 so as to project horizontally. A cam member movement direction

20250415001

detection sensor (position detection means) 57 and a  
cam member area detection sensor (position detection  
means) 58 for detecting the cam member state  
detection flag 105 are mounted on the back side plate  
5 67 of the upper frame 62 in a state of being  
distanced apart from each other along the direction  
of movement of the cam member 72.

The cam member area sensor 58 detects the  
presence/absence of the cam member state detection  
10 flag 105 at its detection point. According to the  
result of this detection, determination is made as to  
whether the cam member 72 is in an area in which it  
operates the punches for three holes punching or in  
an area in which it operates the punches for two  
15 holes punching.

The cam member movement direction sensor 57 also  
detects the presence/absence of the cam member state  
detection flag 105 at its detection point. According  
to the result of this detection, the direction in  
20 which the cam member 72 is driven is determined when  
the cam member 72 is operated to move two or three of  
the punches 68, 68B, 68C, 68D, and 68E for punching.  
(Controller)

The configuration of a controller 110 for  
25 controlling the punching device 50 mounted in the  
finisher 4 will be described with reference to Fig. 5.  
The controller 110 is provided in the processing

20200204-19476001



control device 46 shown in Fig. 1, and incorporates a central processing unit (CPU) 111, a read-only memory (ROM) 112, and a random-access memory (RAM) 113. The controller 110 performs overall control of the punching device 50 on the basis of a control program stored in the ROM 112. The RAM 113 is used as a working area for temporarily holding control data and for arithmetic processing involved in control processing.

10       The cam member HP detection sensor 56, the cam member movement direction sensor 57, and the cam member area detection sensor 58 are connected to the controller 110.

15       Signals representing the results of sensing by these sensors 56, 57 and 58 are input to the controller 110 to be used for control of the punching device 50. The cam member drive motor 92 is a drive source for reciprocating the cam member 72 of the punching device 50 in the horizontal direction to punch holes in a sheet.

20       A driver 114 controls the cam member drive motor 92 according to a control signal from the controller 110. A cam member FG sensor 59 is a sensor for detecting slits in a slit disk 93 attached to a rotating shaft of the cam member drive motor 92. A signal representing the result of sensing by the cam member FG sensor 59 is input to the controller 110.

20240507-154400

From this signal, the controller 110 computes the number of revolutions of the cam member drive motor 92 and the moving distance of the cam member 72.

(Explanation of Operation)

5 Figs. 6A through 6G are diagrams showing the state of the operation of the cam member 72. Fig. 7 is a diagram showing the logical ON/OFF states of the cam member <sup>Home position</sup> HP detection sensor 56, the cam member movement direction sensor 57, and the cam member area  
10 detection sensor 58 relating to the state of the operation of the cam member 72.

The punching operation of the punching device 50 will now be described.

Referring to Fig. 8, which is a flowchart for  
15 explaining the operation of the punching device 50, a control signal for starting the operation is transmitted from the control device 14 (see Fig. 1) in the copying machine main unit 2 to the processing control device 46 for controlling the punching device  
20 50 (S601). The controller 110 in the processing control device 46 for controlling the punching device 50 then executes an operation for initializing the punching device 50 (S602).

(Explanation of Initializing Operation)

25 Fig. 9 is a flowchart for explaining the initializing operation of the punching device.

This initializing operation is an operation for

10091464-030702

setting the cam member in a home position to reliably perform the punching operation. When the initializing operation is started (S602), the controller 110 in the processing control device 46 for controlling the punching device 50 checks the states (ON/OFF) of inputs from the cam member HP detection sensor 56, the cam member movement direction detection sensor 57, and the cam member area detection sensor 58. From the states of the signal inputs from these sensors, the controller 110 identifies one of areas in which the cam member 72 is located.

For example, in a case where the state of the input from the cam member HP detection sensor 56 is OFF; the state of the input from the cam member movement direction detection sensor 57 is ON; and the state of the cam member area detection sensor 58 is ON, the cam member 72 is in a punching area (5) defined as shown in Fig. 7 and the punching device 50 is in the state shown in Fig. 6F. As shown in Fig. 7, there are seven areas occupied by the cam member 72. Selection of a destination to which the cam member 72 should be made to move in the initializing operation depends on the initial area.

Fig. 10 shows a matrix designating a destination according to the states of the inputs from the cam member HP detection sensor 56, the cam member movement direction detection sensor 57, and the cam

20250914 14:54:03.0702

member area detection sensor 58. For example, if the initial area is a rest area (1) or a punching area (2) in the areas shown in Fig. 7, the cam member 72 is moved to a rest area (4). If the initial area is a punching area (3), the cam member 72 is moved to the rest area (1). If the initial area is the rest area (4) or the punching area (5), the cam member 72 is moved to a rest area (7). If the initial area is the punching area (6) or the rest area (7), the cam member 72 is moved to the rest area (4).

Thus, a destination in the initializing operation is determined from the matrix (S702). After determination of a destination, the controller 110 sends a control signal to the motor driver 114 for driving the cam member drive motor 92 (S703).

The control signal for driving the cam member drive motor 92 includes a motor ON signal, a motor normal/reverse rotation signal, and a motor reverse rotation signal. If the number designating the area selected as a destination is larger than that designating the initial area, the cam member 72 is moved from left to right as viewed in Figs. 6A to 6G. In this case, the level of the motor normal/reverse rotation signal is 1 (H level) and the controller 110 causes the motor shaft to move clockwise. If the number designating the area selected as a destination is smaller than that designating the initial area,

20250914B4-030702

the cam member 72 is moved from right to left as viewed in Figs. 6A to 6G. In this case, the level of the motor normal/reverse rotation signal is 0 (L level) and the controller 110 causes the motor shaft  
5 to move counterclockwise.

If a target rotational speed of the cam member drive motor 92 is V1 (which is also a target speed of movement of the cam member 72 since the gear ratio of the rack 91 and the pinion 94 is 1 : 1), the  
10 controller 110 performs rotational speed control of the cam member drive motor 92 so that the rotational speed of the motor 92 becomes equal to the target speed V1. To perform this control, the controller 110 detects the input pulse signal from the cam member FG  
15 sensor 59 and performs pulse width modulation (PWM) control of the motor ON signal.

After starting driving the cam member drive motor 92, the controller 110 starts counting up a timer count T1 with a timer (S704). The controller  
20 110 then determines whether timer count T1 < 300 msec (S705). If T1 < 300 msec, the controller 110 then determines whether the cam member HP detection sensor 56 has become ON (S706). If the cam member HP detection sensor 56 is ON, the controller 110  
25 determines that the cam member 72 has moved to the HP area, and stops the cam member drive motor 92 by stopping transmitting the control signal for driving

10091454-030702

5           If timer count T1  $\geq$  300 msec in step S705, the  
controller 110 determines that the cam member 72  
cannot reach the HP area due to occurrence of some  
abnormality in the operation of the cam member drive  
motor 92 or in the movement of the cam member 72, and  
10 determines this condition as an error of drive of the  
cam member drive motor 92 has occurred (S709). When  
such a drive error occurs, the controller 110 stops  
the punching device 50 to prevent any damage to the  
punching device 50, and displays information  
15 indicating the drive error on a display panel (not  
shown) provided on the sheet processor or the copying  
machine main unit 2 (S710). The controller 110 thus  
completes the initializing operation (S708).

While the initializing operation of the punching device having three HP areas has been described, the  
20 initializing operation of a punching device having two HP areas can be performed in the same manner. That is, in a punching device having two HP areas, the cam member 72, whose operation can be described  
25 with respect to the areas shown in Fig. 7, is moved through the range from the rest area (1) to the rest area (4) or through the range from the rest area (4)

to the rest area (7). The matrix shown in Fig. 10 can also apply in this case.

More specifically, in the case of a punching device in which the cam member 72 is moved through  
5 the range from the rest area (1) to the rest area (4), the cam member 72 is moved to the rest area (4) if it is initially located in the rest area (1) or in the punching area (2), and is moved to the rest area (1) if it is initially located in the punching area (3)  
10 or in the rest area (4).

In the case of a punching device in which the cam member 72 is moved through the range from the rest area (4) to the rest area (7), the cam member 72 is moved to the rest area (7) if it is initially  
15 located in the rest area (4) or in the punching area (5), and is moved to the rest area (4) if it is initially located in the punching area (6) or in the rest area (7).

According to the matrix shown in Fig. 10, in the  
20 initializing operation of the punching devices having three HP areas, the cam member 72 is moved to the rest area (4) if the initial area is the rest area (1) or the punching area (2), is moved to the rest area (1) if the initial area is the punching area (3)  
25 or the rest area (4), is moved to the rest area (7) if the initial area is the rest area (4) or the punching area (5), and is moved to the rest area (4)

202360-4446001

if the initial area is the punching area (6) or the rest area (7), that is, the cam member 72 is moved to the area remoter than the closet area. The cam member 72 is not moved to the rest area (1) when the initial  
5 area is the rest area (1) or the punching area (2), is not moved to the rest area (4) when the initial area is the punching area (3) or the rest area (4), is not moved to the rest area (4) when the initial area is the rest area (4) or the punching area (5),  
10 and is not moved to the rest area (7) when the initial area is the punching area (6) or the rest area (7). That is, the cam member 72 is not moved to the closer area. The reason for moving the cam member to the remoter area is as described below.

15 The cam member drive motor 92 is stopped after the cam member state detection flags 101, 102, 103, and 105 provided on the cam member 72 have been detected by the cam member HP detection sensor 56, the cam member movement direction detection sensor 57,  
20 and the cam member area detection sensor 58. Therefore, the cam member cannot be stopped in the desired area unless it always passes the sensors with the same inertia. If the cam member 72 is moved to the closer area, it must be stopped immediately.  
25 However, the inertia of the cam member 72 thus moved is not always the same.

If the inertia is not always the same, the cam

10091464-030702



member 72 cannot be stopped at the target area with accuracy, that is, initialization cannot be performed with the desired accuracy. For this reason, the cam member 72 is stopped after being moved through a certain distance, thereby ensuring that the inertia of the cam member 72 when the cam member drive motor 92 is stopped is substantially the same no matter which initial area the cam member 72 has started moving from. The lengths of the cams 73A, 73B, 73C, 73D, and 73E formed in the cam member 72 are utilized to enable movement of the cam member 72 through a certain distance, thereby avoiding increasing the overall size of the punching device.

The same can also be said with respect to the initializing operation of the punching devices having only two HP areas.

Referring again to Fig. 8, after the initializing operation (S602) has been completed, a job start signal is transmitted from the control device 14 (see Fig. 1) in the copying machine main unit 2 to the processing control device 46 for controlling the punching device 50. Simultaneously, sheet size information designating the size of a sheet conveyed from the copying machine main unit 2 to the punching device 50 is transmitted to the processing control device 46. Sheet size information is transmitted each time a sheet is conveyed from the

20250304-15416001

If the sheet size data obtained in step S605 designates a punchable sheet size, the controller 110 checks the cam member 72 area. The result of the above-described initializing operation (S602) must be that the cam member 72 has been moved to the rest area (1), the rest area (4) or the rest area (7) shown in Fig. 7. That is, the controller 110 determines the location of the cam member 72 in one of the rest area (1), the rest area (4), and the rest area (7) shown in Fig. 7. This determination is made through detection of the ON/OFF state of the cam member HP detection sensor 56 (S606).

If no determination result indicating the  
25 location of the cam member 72 in one of the rest area  
(1), the rest area (4), and the rest area (7) is  
obtained, it is not possible to assure the desired

result of the punching operation, and the controller 110 determines that an error of drive of the cam member drive motor 92 has occurred (S617). When such a drive error occurs, the controller 110 stops the punching device 50 to prevent any damage to the punching device 50, and displays information indicating the drive error on the display panel (not shown) provided on the sheet processor or the copying machine main unit 2 (S618). If it is determined in S606 that the cam member 72 is in one of the rest area (1), the rest area (4), and the rest area (7), the controller 110 advances the process to the next step of determining the sheet width (S607).

In the sheet width determination step S607, detection is performed with a sensor (not shown) to determine whether the sheet width data W in the sheet size data obtained in step S604 is within the range defined by  $266 < W < 298$ . If the sheet width data W is  $266 < W < 298$ , the controller 110 determines that the sheet size designated by the sheet size data is the size of a sheet in which three holes are to be punched. If the sheet width data W is out of the range, the controller 110 determines that the sheet size designated by the sheet size data is the size of a sheet in which two holes are to be punched. Three holes may be also punched in a case where the sheet width data is  $266 < W$ .

20%0E0-454F600F

If the result of sheet width determination in step S607 is that the sheet width data  $W$  is  $266 < W < 298$ , the controller 110 determines whether the cam member 72 is in one of the areas in which it can be operated to punch three holes (S608). For example, if the controller 110 determines that the cam member 72 is in the rest area (4) or the rest area (7) shown in Fig. 7, it starts a three holes punching operation (S610), which is described below. If the controller 110 determines in step S608 that the cam member 72 is in the rest area (1) shown in Fig. 7, it performs two holes/three holes switching operation (S609), which is also described below, since three holes punching cannot be directly started.

15 Further, if the result of sheet width determination in step S607 is that the sheet width data  $W$  is out of the range  $266 < W < 298$ , the controller 110 determines whether the cam member 72 is in one of the areas in which it can be operated to punch two holes (a first number of holes (or a second number of holes)) (S612). For example, if the controller 110 determines that the cam member 72 is in the rest area (1) or the rest area (4) shown in Fig. 7, it starts a two holes punching operation (S614), which is described below. If the controller 110 determines in step S612 that the cam member 72 is in the rest area (7) shown in Fig. 7, it performs

three holes/two holes switching operation (S613), which is also described below, since two holes punching cannot be directly started.

After the punching operation has been performed,  
5 the controller determines whether there is a job continuation signal from the control device 14 (see Fig. 1) in the copying machine main unit 2 to the processing control device 46 for controlling the punching device 50 (S615). If there is a job  
10 continuation signal, the controller 110 returns the process to step S604 to obtain sheet size data designating the size of the next sheet (S604). If the controller 110 determines in step S615 that there is no job continuation signal, it recognizes the end of  
15 the job and terminates the sequential punching process (S616).

(Three holes Punching Operation)

The operation for punching three holes (the second number of holes (or the first number of  
20 holes)) in a sheet will be described with reference to the flowchart of Fig. 11.

(Three holes Punching Normal Rotation Control)

When a sheet P is conveyed to the punching device, it is guided into the gap S. Thereafter, the  
25 operation of the pair of rollers (not shown) conveying the sheet P is stopped to set the sheet in such a position that the end of the sheet on the

20200304-15446001

upstream side faces the punches 68A, 68B, 68C, 68D,  
and 68E. At this time, if the cam member 72 is in the  
rest area (7) shown in Fig. 7 (S900), it is in the  
state of being shifted rightward relative to the  
5 movable frame 52, as shown in Fig. 6G.

To enable punching of holes in the sheet, it is  
necessary to move the cam member 72 leftward from the  
right-hand position. The controller 110 controls the  
cam member drive motor 92 so that the cam member 72  
10 moves from right to left as viewed in Fig. 6G.  
Control for moving the cam member 72 such as moving  
from the rest area (7) toward the rest area (4) will  
be referred to as three holes normal rotation control.

In step S610, when conveyance of sheet P by the  
15 pair of rollers (not shown) is stopped, the  
controller 110 sends a control signal to the motor  
driver 114 for driving the cam member drive motor 92  
(S901). The control signal for driving the cam member  
drive motor 92 comprises a motor ON signal, a motor  
20 normal/reverse rotation signal, and a motor reverse  
rotation signal. In the case of normal rotation  
control, the level of the motor normal/reverse  
rotation signal is 1 (H level) and the motor shaft is  
rotated clockwise.

25 If a target rotational speed of the cam member  
drive motor 92 is V2 (which is also a target speed of  
movement of the cam member 72), the controller 110

2020000-1971000

performs rotational speed control of the cam member drive motor 92 (S902) through PWM control of the motor ON signal so that the rotational speed of the cam member drive motor 92 becomes equal to the target speed V2. The controller 110 performs this control by detecting the input pulse signal from the cam member FG sensor 59 (S903).

After starting driving the cam member drive motor 92, the controller 110 starts counting up by a timer count T2 (S905). This counting-up of timer count T2 is performed for the purpose of detecting a failure in the operation of the cam member drive motor 92. While processing is continued in step S905 and subsequent steps, the timer and the controller 110 always monitor the cam member drive motor 92 in cooperation with each other. If  $T2 \geq 200$  msec (S906), the controller 110 determines that the operation of the cam member drive motor 92 has ended in failure due to occurrence of some abnormality in the operation of the cam member drive motor 92 or in the movement of the cam member 72, and determines this condition as an error of drive of the cam member drive motor 92 (S907). When such a drive error occurs, the controller 110 stops the punching device 50 to prevent any damage to the punching device 50, and displays information indicating the drive error on the display panel (not shown) provided on the sheet

202504-030702

processor or the copying machine main unit 2 (S914).

As the cam member drive motor 92 rotates, the cam member 72 is moved from right to left in the order of Fig. 6G, Fig. 6F, Fig. 6E, and Fig. 6D by means of the pinion 93 and the rack 91. With this movement, the punches 68A, 68B, and 68C for punching there holes are moved downward by the three-holes punching cams 73A, 73B, and 73C to punch three holes in the sheet and are then moved upward.

The controller 110 then waits for turning-off of the cam member HP detection sensor 56 (S908). When the cam member HP detection sensor 56 becomes OFF in step S908, the controller 110 starts counting-up the number of pulses P1 from the cam member FG sensor 59 (S909). When during the advancement of motor drive the number of pulses P1 from the cam member FG sensor 59 becomes, for example,  $P1 = 94$  (S910), the controller 110 stops the drive control signal to the cam member drive motor 92, thereby stopping the cam member drive motor 92 (S911).

The number of pulses, which is 94, at which the cam member drive motor 92 is stopped by the controller 110 is selected by considering mechanical variations in the punching device 50 and variations in motor characteristics. That is, the number of pulses is set to such a number that the cam member 72 can be reliably stopped within the rest area (4)

10091464-030702



shown in Fig. 7. During counting-up to this number,  
the cam member HP detection sensor 56 becomes  
temporarily "OFF" from the state of being turned "ON"  
by the punching operation state detection flag 101 at  
5 the left end in the three punching operation state  
detection flags 101, 102, and 103, and is thereafter  
returned to the "ON" state by the central punching  
state detection flag 102.

Even if the cam member drive motor is turned OFF,  
10 the cam member 72 stop timing is adjusted by  
factoring in the inertia of the cam member drive  
motor 92, the inertia of the cam member 72, etc., so  
that the cam member 72 is stopped with the cam member  
HP detection sensor 56 correctly facing the central  
15 punching operation state detection flag 102 (the cam  
member 72 in the rest area (4) shown in Fig. 7)  
(S912).

(Three holes Punching Reverse Rotation Control)

When a sheet P is conveyed to the punching  
20 device, it is guided into the gap S. Thereafter, the  
operation of the pair of rollers (not shown)  
conveying the sheet P is stopped to set the sheet in  
such a position that the end of the sheet on the  
upstream side faces the punches 68A, 68B, 68C, 68D,  
25 and 68E. At this time, if the cam member 72 is in the  
rest area (4) shown in Fig. 7, it is in the state of  
being shifted leftward relative to the movable frame

202504-0300

52, as shown in Fig. 6D.

To enable punching of holes in the sheet, it is necessary to move the cam member 72 rightward from the left-hand position. The controller 110 controls the cam member drive motor 92 so that the cam member 72 moves from left to right as viewed in Fig. 6D. Control for moving the cam member 72 such as moving from the rest area (4) toward the rest area (7) will be referred to as three holes reverse rotation control.

In step S610, when conveyance of sheet P by the pair of rollers (not shown) is stopped, the controller 110 sends a control signal to the motor driver 114 for driving the cam member drive motor 92 (S901). The control signal for driving the cam member drive motor 92 comprises a motor ON signal, a motor normal/reverse rotation signal, and a motor reverse rotation signal. In the case of normal rotation control, the level of the motor normal/reverse rotation signal is 0 (L level) and the motor shaft is rotated counterclockwise.

If a target rotational speed of the cam member drive motor 92 is V2 (which is also a target speed of movement of the cam member 72), the controller 110 performs rotational speed control of the cam member drive motor 92 (S902) through PWM control of the motor ON signal so that the rotational speed of the

202504-434600F

cam member drive motor 92 becomes equal to the target speed V2. The controller 110 performs this control by detecting the input pulse signal from the cam member FG sensor 59 (S903).

- 5           After starting driving the cam member drive motor 92, the controller 110 starts counting up by a timer count T2 (S905). This counting-up of timer count T2 is performed for the purpose of detecting a failure in the operation of the cam member drive
- 10 motor 92. While processing is continued in step S905 and subsequent steps, the timer and the controller 110 always monitor the cam member drive motor 92 in cooperation with each other. If  $T2 \geq 200$  msec (S906), the controller 110 determines that the operation of
- 15 the cam member drive motor 92 has ended in failure due to occurrence of some abnormality in the operation of the cam member drive motor 92 or in the movement of the cam member 72, and determines this condition as an error of drive of the cam member
- 20 drive motor 92 (S907). When such a drive error occurs, the controller 110 stops the punching device 50 to prevent any damage to the punching device 50, and displays information indicating the drive error on the display panel (not shown) provided on the sheet
- 25 processor or the copying machine main unit 2 (S914).

As the cam member drive motor 92 rotates, the cam member 72 is moved from left to right in the

20250314-0300T

order of Fig. 6D, Fig. 6E, Fig. 6F, and Fig. 6G by means of the pinion 93 and the rack 91. With this movement, the punches 68A, 68B, and 68C for punching three holes are moved downward by the three-holes  
5 punching cams 73A, 73B, and 73C to punch three holes in the sheet and are then moved upward.

The controller 110 then waits for turning-off of the cam member HP detection sensor 56 (S908). When the cam member HP detection sensor 56 becomes OFF in  
10 step S908, the controller 110 starts counting-up the number of pulses P1 from the cam member FG sensor 59 (S909). When during the advancement of motor drive the number of pulses P1 from the cam member FG sensor 59 becomes, for example, P1 = 94 (S910), the  
15 controller 110 stops the drive control signal to the cam member drive motor 92, thereby stopping the cam member drive motor 92 (S911).

The number of pulses, which is 94, at which the cam member drive motor 92 is stopped by the  
20 controller 110 is selected by considering mechanical variations in the punching device 50 and variations in motor characteristics. That is, the number of pulses is set to such a number that the cam member 72 can be reliably stopped within the rest area (7)  
25 shown in Fig. 7. During counting-up this number, the cam member HP detection sensor 56 becomes temporarily "OFF" from the state of being turned "ON" by the

20200204-1454-030702

central punching operation state detection flag 102  
in the three punching operation state detection flags  
101, 102, and 103, and is thereafter returned to the  
"ON" state by the punching operation state detection  
5 flag 101 at the left end.

Even if the cam member drive motor 92 is turned  
OFF, the cam member 72 stop timing is adjusted by  
factoring in the inertia of the cam member drive  
motor 92, the inertia of the cam member 72, etc., so  
10 that the cam member 72 is stopped with the cam member  
HP detection sensor 56 correctly facing the punching  
operation state detection flag 101 at the left end  
(the cam member 72 in the rest area (7) shown in Fig.  
7) (S912).

15 (Two holes Punching Operation)

The operation for punching two holes in a sheet  
will be described with reference to the flowchart of  
Fig. 12.

(Two holes Punching Normal Rotation Control)

20 When a sheet P is conveyed to the punching  
device, it is guided into the gap S. Thereafter, the  
operation of the pair of rollers (not shown)  
conveying the sheet P is stopped to set the sheet in  
such a position that the end of the sheet on the  
25 upstream side faces the punches 68A, 68B, 68C, 68D,  
and 68E. At this time, if the cam member 72 is in the  
rest area (4) shown in Fig. 7 (S1000), it is in the

state of being shifted rightward relative to the movable frame 52, as shown in Fig. 6D.

To enable punching of holes in the sheet, it is necessary to move the cam member 72 leftward from the right-hand position. The controller 110 controls the cam member drive motor 92 so that the cam member 72 moves from right to left as viewed in Fig. 6D. Control for moving the cam member 72 such as moving from the rest area (4) toward the rest area (1) will be referred to as two holes normal rotation control.

In step S614, when conveyance of sheet P by the pair of rollers (not shown) is stopped, the controller 110 sends a control signal to the motor driver 114 for driving the cam member drive motor 92 (S1001). The control signal for driving the cam member drive motor 92 comprises a motor ON signal, a motor normal/reverse rotation signal, and a motor reverse rotation signal. In the case of normal rotation control, the level of the motor normal/reverse rotation signal is 1 (H level) and the motor shaft is rotated clockwise.

If a target rotational speed of the cam member drive motor 92 is V2 (which is also a target speed of movement of the cam member 72) (S1002), the controller 110 performs rotational speed control of the cam member drive motor 92 (S1002) through PWM control of the motor ON signal so that the rotational

20250704 14:44:00

speed of the cam member drive motor 92 becomes equal to the target speed V2. The controller 110 performs this control by detecting the input pulse signal from the cam member FG sensor 59 (S1003).

5           After starting driving the cam member drive motor 92, the controller 110 starts counting up by a timer count T2 (S1005). This counting-up of timer count T2 is performed for the purpose of detecting a failure in the operation of the cam member drive  
10 motor 92. While processing is continued in step S1005 and subsequent steps, the timer and the controller 110 always monitor the cam member drive motor 92 in cooperation with each other. If  $T2 \geq 200$  msec (S1006), the controller 110 determines that the operation of  
15 the cam member drive motor 92 has ended in failure due to occurrence of some abnormality in the operation of the cam member drive motor 92 or in the movement of the cam member 72, and determines this condition as an error of drive of the cam member  
20 drive motor 92 (S1007). When such a drive error occurs, the controller 110 stops the punching device 50 to prevent any damage to the punching device 50, and displays information indicating the drive error on the display panel (not shown) provided on the  
25 sheet processor or the copying machine main unit 2 (S1014).

As the cam member drive motor 92 rotates, the

10091464-030202

cam member 72 is moved from right to left in the order of Fig. 6D, Fig. 6C, Fig. 6B, and Fig. 6A by means of the pinion 93 and the rack 91. With this movement, the punches 68D and 68E for punching two  
5 holes are moved downward by the two-holes punching cams 73D and 73E to punch two holes in the sheet and are then moved upward.

The controller 110 then waits for turning-off of the cam member HP detection sensor 56 (S1008). When  
10 the cam member HP detection sensor 56 becomes OFF in step S1008, the controller 110 starts counting-up the number of pulses P2 from the cam member FG sensor 59 (S1009). When during the advancement of motor drive the number of pulses P2 from the cam member FG sensor  
15 59 becomes, for example,  $P2 = 83$  (S1010), the controller 110 stops the drive control signal to the cam member drive motor 92, thereby stopping the cam member drive motor 92 (S1011).

The number of pulses, which is 83, at which the  
20 cam member drive motor 92 is stopped by the controller 110 is selected by considering mechanical variations in the punching device 50 and variations in motor characteristics. That is, the number of pulses is set to such a number that the cam member 72  
25 can be reliably stopped within the rest area (1) shown in Fig. 7. During counting-up to this number, the cam member HP detection sensor 56 becomes

20250000-4946001



temporarily "OFF" from the state of being turned "ON" by the central punching operation state detection flag 102 in the three punching operation state detection flags 101, 102, and 103, and is thereafter  
5 returned to the "ON" state by the punching operation state detection flag 103 at the right end.

Even if the cam member drive motor 92 is turned OFF, the cam member 72 stop timing is adjusted by factoring in the inertia of the cam member drive  
10 motor 92, the inertia of the cam member 72, etc., so that the cam member 72 is stopped with the cam member HP detection sensor 56 correctly facing the punching operation state detection flag 103 at the right end (the cam member 72 in the rest area (1) shown in Fig.  
15 7) (S1012).

(Two holes Punching Reverse Rotation Control)

When a sheet P is conveyed to the punching device, it is guided into the gap S. Thereafter, the operation of the pair of rollers (not shown)  
20 conveying the sheet P is stopped to set the sheet in such a position that the end of the sheet on the upstream side faces the punches 68A, 68B, 68C, 68D, and 68E. At this time, if the cam member 72 is in the rest area (1) shown in Fig. 7 (S1000), it is in the  
25 state of being shifted leftward relative to the movable frame 52, as shown in Fig. 6A.

To enable punching of holes in the sheet, it is

2020E0-49415001

necessary to move the cam member 72 rightward from the left-hand position. The controller 110 controls the cam member drive motor 92 so that the cam member 72 moves from left to right as viewed in Fig. 6A.

- 5 Control for moving the cam member 72 such as moving from the rest area (1) toward the rest area (4) will be referred to as two holes reverse rotation control.

In step S614, when conveyance of sheet P by the pair of rollers (not shown) is stopped, the  
10 controller 110 sends a control signal to the motor driver 114 for driving the cam member drive motor 92 (S1001). The control signal for driving the cam member drive motor 92 comprises a motor ON signal, a motor normal/reverse rotation signal, and a motor  
15 reverse rotation signal. In the case of normal rotation control, the level of the motor normal/reverse rotation signal is 0 (L level) and the motor shaft is rotated counterclockwise.

If a target rotational speed of the cam member  
20 drive motor 92 is V2 (which is also a target speed of movement of the cam member 72) (S1002), the controller 110 performs rotational speed control of the cam member drive motor 92 (S1002) through PWM control of the motor ON signal so that the rotational  
25 speed of the cam member drive motor 92 becomes equal to the target speed V2. The controller 110 performs this control by detecting the input pulse signal from

202307-15415001

the cam member FG sensor 59 (S1003).

After starting driving the cam member drive motor 92, the controller 110 starts counting up by a timer count T2 (S1005). This counting-up of timer  
5 count T2 is performed for the purpose of detecting a failure in the operation of the cam member drive motor 92. While processing is continued in step S1005 and subsequent steps, the timer and the controller 110 always monitor the cam member drive motor 92 in  
10 cooperation with each other. If  $T2 \geq 200$  msec (S1006), the controller 110 determines that the operation of the cam member drive motor 92 has ended in failure due to occurrence of some abnormality in the operation of the cam member drive motor 92 or in the  
15 movement of the cam member 72, and determines this condition as an error of drive of the cam member drive motor 92 (S1007). When such a drive error occurs, the controller 110 stops the punching device 50 to prevent any damage to the punching device 50,  
20 and displays information indicating the drive error on the display panel (not shown) provided on the sheet processor or the copying machine main unit 2 (S1014).

As the cam member drive motor 92 rotates, the  
25 cam member 72 is moved from left to right in the order of Fig. 6A, Fig. 6B, Fig. 6C, and Fig. 6D by means of the pinion 93 and the rack 91. With this

2020E0-49476001

movement, the punches 68D and 68E for punching two holes are moved downward by the two-holes punching cams 73D and 73E to punch two holes in the sheet and are then moved upward.

5           The controller 110 then waits for turning-off of the cam member HP detection sensor 56 (S1008). When the cam member HP detection sensor 56 becomes OFF instep S1008, the controller 110 starts counting-up the number of pulses P2 from the cam member FG sensor  
10 59 (S1009). When during the advancement of motor drive the number of pulses P2 from the cam member FG sensor 59 becomes, for example,  $P2 = 83$  (S1010), the controller 110 stops the drive control signal to the cam member drive motor 92, thereby stopping the cam  
15 member drive motor 92 (S1011).

          The number of pulses, which is 83, at which the cam member drive motor 92 is stopped by the controller 110 is selected by considering mechanical variations in the punching device 50 and variations  
20 in motor characteristics. That is, the number of pulses is set to such a number that the cam member 72 can be reliably stopped within the rest area (4) shown in Fig. 7. During count to this number, the cam member HP detection sensor 56 becomes temporarily  
25 "OFF" from the state of being turned "ON" by the punching operation state detection flag 103 at the right end in the three punching operation state

2020000-4946001

detection flags 101, 102, and 103, and is thereafter returned to the "ON" state by the central punching operation state detection flag 102.

204380-43715001  
5 The cam member 72 stop timing is adjusted by factoring in the inertia of the cam member drive motor 92, the inertia of the cam member 72, etc., so that the cam member 72 is stopped with the cam member HP detection sensor 56 correctly facing the central punching state detection flag 102 (the cam member 72 in the rest area (4) shown in Fig. 7) (S1012).  
10 (Two holes/three holes Switching Operation)

The operation for switching the number of holes to be punched in a sheet from two to three will be described with reference to the flowchart of Fig. 13.

15 In the case where three holes punching operation in step S610 shown in Fig. 8 is continued, that is, the sheet width size data checked in step S607 is unchanged, punching of three holes in a sheet in the above-described manner can be repeated by  
20 reciprocating the cam member 72 between the rest area (4) and the rest area (7) shown in Fig. 7. Similarly, in the case of two holes punching, punching of two holes in a sheet can be repeated by reciprocating the cam member 72 between the rest area (1) and the rest  
25 area (4) shown in Fig. 7.

Therefore, if in step S607 the sheet width size data is changed from a value out of the range  $266 < W$

< 298 to a value within the range  $266 < W < 298$ , it is necessary to change the punching mode from two holes punching operation to three holes punching operation.

5 Referring to Fig. 13, if the cam member 72 is located in one of the areas other than the rest area (4) shown in Fig. 7 (S1021), it is moved to the rest area (4) shown in Fig. 7 (S1022). If the cam member 72 is located in the rest area (4) shown in Fig. 7,  
10 it is not moved from the rest area (4) since it can be immediately operated for either two holes or three holes punching operation from the rest area (4). The cam member control method for moving the cam member from the rest area (7) to the rest area (4) is the  
15 same as that for the above-described two holes reverse rotation operation.

(Three holes/two holes Switching Operation)

Conversely, if in step S607 the sheet width size data is changed from a value within the range  $266 < W$   
20 < 298 to a value out of the range  $266 < W < 298$ , it is necessary to change the punching mode from three holes punching operation to two holes punching operation.

Referring to Fig. 13, if the cam member 72 is  
25 located in one of the areas other than the rest area (4) shown in Fig. 7 (S1021), it is moved to the rest area (4) shown in Fig. 7 (S1022). If the cam member

20202020-49476001

5

10

20

25

5           The reason for setting the target speed V1 of  
the cam member drive motor 92 (corresponding to the  
target speed of movement of the cam member 72) in the  
initializing operation to a value lower than the  
target speed V2 of the cam member 72 in the punching  
10 operation in the above description is as described  
below.

The area in which the cam member 72 is stopped immediately before the initializing operation is performed is not fixed. The distance through which the cam member 72 is moved from the area in which it has been stopped to the area in which it is stopped at the end of the initializing operation varies on a case-by-case basis. It is difficult to control stopping of the cam member 72 through the rotation of the cam member drive motor 92, which is a pulse motor. In view of this problem, the cam member 72 is stopped after the cam member drive motor 92 is stopped upon detecting the cam member state detection flags 101, 102, 103, and 105 provided on the cam member 72 by means of the cam member HP detection sensor 56, the cam member movement direction detection sensor 57, and the cam member area detection sensor 58.



Therefore, if the speed of movement of the cam member 72 is increased, the distance through which the cam member 72 moves until the time at which the motor is stopped is increased by the inertia of the cam member 72. In such a case, the time required to thereafter start the punching operation is increased. For this reason, the speed of the cam member drive motor 92 in the initializing operation is reduced to reduce the speed of movement of the cam member 72.

On the contrary, in the case of the punching operation, the distance between one of the rest areas to another of the rest areas via the target punching area is known before the cam member 72 is moved. Therefore, by detecting the number of revolutions of the cam member drive motor 92 and by factoring in the inertia of the cam member drive motor 92, the inertia of the cam member 72, etc., the cam member drive motor 92 may be stopped immediately before the cam member 72 reaches the rest area after passing the target punching area. Consequently, the target speed  $V_2$  of the cam member drive motor 92 in the punching operation is set higher than the target speed  $V_1$  in the initializing operation to improve the punching efficiency.

How the rest areas and punching areas in the appended claims corresponds to the rest areas and punching areas in the above-described embodiment (see

2020E0-494E001

If the rest area (1) in the embodiment is assumed to correspond to the first rest area in claims 1 and 2, the first punching area, the second punching area, and the second rest area in the claims correspond to the punching area (2), the punching area (3), and the rest area (4) in the embodiment.

If the rest area (7) in the embodiment is assumed to correspond to the first rest area in claims 1 and 2, the first punching area, the second punching area, and the second rest area in the claims correspond to the punching area (6), the punching area (5), and the rest area (4) in the embodiment.

If the rest area (1) in the embodiment is assumed to correspond to the first rest area in claims 3 and 4, the first punching area, the second punching area, the second rest area, the third punching area, the fourth punching area, and the third rest area in the claims correspond to the

punching area (2), the punching area (3), the rest area (4), the punching area (5), the punching area (6), and the rest area (7) in the embodiment.

If the rest area (7) in the embodiment is  
5 assumed to correspond to the first rest area in claims 3 and 4, the first punching area, the second punching area, the second rest area, the third punching area, the fourth punching area, and the third rest area in the claims correspond to the  
10 punching area (6), the punching area (5), the rest area (4), the punching area (3), the punching area (2), and the rest area (1) in the embodiment.

The first movement area in the claims is, for example, an area for punching two (or three) holes in  
15 a sheet, and the second movement area is an area for punching three (or two) holes in a sheet. That is, different numbers of holes are punched through the first and second movement areas. The number of holes punched through each of the first and second movement  
20 areas is not limited to two or three. Accordingly, the number of holes punched by the punching device is not limited to two or three.

202002-43416001